


EARTHWOOL ACOUSTIC ROLL

November 2017



APPLICATIONS



DESCRIPTION

Earthwool Acoustic Roll is a flexible glass mineral wool quilt which is lightweight, flexible, resilient and non-combustible. Earthwool Acoustic Rolls are 1200mm wide and ready-cut to produce three, 400mm wide rolls, or two, 600mm wide rolls and manufactured to a minimum density of 10Kg/m³.

PERFORMANCE

Fire

Classification: EUROCLASS A1 to BS EN 13501-1.

Vapour resistivity

Water vapour resistivity: 5.00MN_s/g.m.

BENEFITS

- ✓ Exceptional acoustic absorption properties.
- ✓ Lightweight, and easy to install
- ✓ Dimensioned to suit studs and joists at 400mm or 600mm centres
- ✓ Long roll lengths for quick and economic installation
- ✓ Friction fits between studs, ensuring continuity of the absorbent layer with no air gaps

SPECIFICATIONS

Thickness (mm)	Length (m)	Width (mm)	Area per pack (m ²)	NRC
100	9.17	1200 (2x600)	11.00	1.04
75	12.50	1200 (2x600)	15.00	0.93
63	15.00	1200 (2x600)	18.00	0.89e
50	13.00	1200 (2x600)	15.60	0.83

24 rolls per pallet.
e=estimate

CERTIFICATION



challenge.
create.
care.

EARTHWOOL ACOUSTIC ROLL

November 2017

ADDITIONAL INFORMATION

Durability

Earthwool Acoustic Roll is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Application

Earthwool Acoustic Roll is specifically designed for friction fitting between joists and studs at 400mm and 600mm centres to improve the sound insulation of:

- separating walls and floors
- internal walls and floors
- timber and metal stud partitions

Earthwool Acoustic Roll is also designed for friction fitting between resilient timber battens and timber studs in Robust Detail separating floors and walls.

Earthwool Acoustic Roll provides a high level of sound absorption, whilst also improving the thermal and fire performance of the wall, floor or partition.

Using glass mineral wool as a sound absorbent layer in partitions and floors significantly improves their acoustic performance, whilst only adding minimally to the overall mass of the structure. In partitions glass mineral wool complements the plasterboard linings by absorbing airborne sound in the cavity and reducing reverberation, it is particularly effective at preventing the hollow sound that can occur in partitions with unfilled cavities.

Standards

Earthwool Acoustic Roll is manufactured in accordance with BS EN 13162, EN 50001 Energy Management Systems, OHSAS 18001 Occupational Health and Safety Management Systems, ISO 14001 Environmental Management Systems, and ISO 9001 Quality Management Systems, as certified by Bureau Veritas.

Environmental

Earthwool Acoustic Roll represents no known threat to the environment and has zero Ozone Depletion Potential and zero Global Warming Potential.

Handling and storage

Earthwool Acoustic Roll is easy to handle and install, being lightweight and easily cut to size, where necessary. It is supplied enclosed in polythene which is designed for short term protection only. For longer term protection on site, the product should be stored either indoors, or under cover and off the ground. Earthwool Acoustic Roll should not be left permanently exposed to the elements.



Knauf Insulation mineral wool products made with ECOSE Technology® benefit from a no added formaldehyde binder, which is up to 70% less energy intensive than traditional binders and is made from rapidly renewable bio-based materials instead of petroleum-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Insulation products made with ECOSE Technology® contain no dye or artificial colours.

Knauf Insulation Ltd

PO Box 10, Stafford Road, St.Helens,
Merseyside, WA10 3NS. UK

Customer Service (sales): +44 (0)1744 766 767
export.sales@knaufinsulation.com

Technical Support Team: +44 (0)1744 766 666
technical.uk@knaufinsulation.com

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINE3582DAT - V1117

challenge.
create.
care.