



### Steeple (double-side) Technical data

#### Character

Good adaptive capacity on site. Adjust to the error of ceiling and floor  
 Modular production, quick installation, easy to maintainance  
 Steel panel is available, which can reach the high level fireproof rate

#### Size

Partition module width: 900, 1000, 1100, 1200mm  
 The maximum height of partition: 5000mm  
 The thickness of partition: 100mm  
 The tolerance of adjustment error: ±25mm

#### Panel

0.8mm pre-coated steel panel+12mm plaster board

(Steel Reinforce panel)

Glass panel with aluminum frame; 6mm double glass (exposed frame, hidden frame is optional)

#### Blind

Roll-up blind, 25m wide blind  
 electric blind, 25m wide blind

#### Hardware Accessory

Fastener: on-site plastering, spraying, anti-rust treatment separately according to material itself.  
 Getting necessary brands: DORMA, SELBO

#### Character



The sound insulation index of Plainka office partitions: 41-49 dB with insulator  
 Profile adopts stainless steel, which has a good performance on hardness and anticorrosive resistance

#### Quality

The designing, manufacturing, producing and selling all pass certificate of Quality Management System ISO9001:2008 and Environment Management System 14001:2004. We guarantee the product's quality



### Steeple (double-side) Technical data



### Steeple (double-side) Technical data

